

Norol Perfekt

Wall and ceiling paints for indoor use



AREAS OF APPLICATION

Colour design of interior walls.

PRODUCT PROPERTIES

- Airless spraying possible
- Free of fogging active substances
- Low-noise
- Solvent and softener free
- Matt
- Degree of opacity 1 according to DIN EN 13300
- Wet abrasion resistance 3 according to DIN EN 13300 (washable)
- Tested for harmful substances according to TÜV (Technical Control Board) certificate
- Water-vapour permeable

TECHNICAL DATA

Binder base	Synthetic dispersion
Density	approx. 1,6 kg/l
Diffusion-equivalent air-layer thickness	$s_d < 0,1$ m
VOC value	EU limit value for the VOC content of this product (cat. A/a): 30 g/l (2010). This product contains < 1 g/l VOC.

APPLICATION INSTRUCTIONS

Substrate pre-treatment	All substrates must be stable, clean and free of any residue, which can reduce adhesiveness. Absorbent substrates to be reinforced must be primed with Hydro penetrating primer. Primer can be deluted with max. 1:2 water depending on absorbance of
-------------------------	--

substrate.

Application	Apply Norol fully wetted and even in one coating. Can be diluted up to 3 %. A baselayer coat (diluted up to max. 5 %) can be advisable for surfaces with a high contrast. Apply material wet-in-wet in a cross motion. Spray application is possible.
Consumption	approx. 160 - 200 ml per layer per m ² Determine the precise material requirements by means of a trial coating on the object.
Information about the weather	The material, substrate and air temperatures cannot fall below +5 °C during application and drying.
Drying time	approx. 2 - 6 hours Depending on temperature, relative humidity and substrate conditions even longer.
Cleaning of tools	In a fresh state with soap and water.

STORAGE

Shelf life in original sealed packaging of at least 1 year when kept cool and protected against frost.

PACKAGING INFORMATION

Information about batches	The accuracy of the colour blend must be checked prior to application; objections to the colouring cannot be taken into account after application. Slight colour variations must be accepted within different batches and for a reordering of special colours. Only use products from one batch on closed surfaces; if required, mix.
Colour	White, antique white and pigmented
Packaging unit	PP bucket approx. 15 l

OTHER INFORMATION

Information on safety	The information provided in the current safety data sheet applies.
Transportation	Not a hazardous material
Giscode	M-DF01 latex paints, solvent-free

alsecco GmbH
Kupferstraße 50
D-36208 Wildeck
Phone 03 69 22 / 88-0
Fax 03 69 22 / 88-330
Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.



FASSADENKOMPETENZ